CO-W121C/P2002 Series

21.5" 6th Gen. Intel® Core™ Processor U Series Fanless Touch Panel PC with CFM & CDS Technology



ALL-NEW OPEN FRAME PANEL PC

| CO-100/P2002 Series Fits Any Machine Perfectly |

Overview

CONTACT

Cincoze's high-performance open-frame modular panel PCs (CO-W121C/P2002 Series) use Intel® Core U series processors that provide high-performance data processing and graphics computing capabilities with only 15W low power consumption. The CO-100/P2002 series supports CFM technology that extends system functions according to requirements, with options such as Power Ignition Sensing (IGN) and Power over Ethernet (PoE). The series has multiple sizes, display ratios (4:3 and 16:9), and touchscreen options. Its integrated structure, exclusive adjustable mounting bracket, and support for multiple mounting methods to perfectly fit cabinets of different materials and thicknesses. The robust design also meets the application needs of harsh industrial environments.

Key Features

- 21.5" TFT-LCD with Projected Capacitive Touch
- Onboard Intel® 6th Generation Core™ Processor U Series (15W)
- 2x DDR4 SO-DIMM Socket, Support Up to 32 GB
- Designed with Adjustable Mounting Bracket
- Support Flat / Standard / VESA / Rack Mount
- Front Panel IP65 Compliant
- Wide Operating Temperature
- Cincoze Patent CDS Technology Support


Certifications

IP65

High Performance and Power Saving

Intel® Core U series processors provide high-performance data processing and graphics computing capabilities with a 15W low power consumption, support for up to 64GB of memory and two 2.5" HDD/SSD.

15W TDP CPU Design



Patented CDS Technology

The patented CDS (Convertible Display System) technology makes maintenance easy and offers flexibility for future upgrades. To upgrade the panel size, replace the display module, or to upgrade the system performance, replace the computer module.


Patent No. M482908

Flexibility for Various Applications

Mini-PCIe and PCI/PCIe expansion slots support data acquisition cards, motion control cards, I/O expansion, and other applications.

[PCI/PCIe expansion slot available Model : CO- W121C/P2002E]





Flexible Design and Easy Installation

Exclusive adjustable mounting bracket with thickness adjustment setting and two panel-locking methods (panel or boss type) make modular panel PC easier and more convenient to integrate into industrial machinery.

Patent No.: D224544, D224545, I802427

Integrated Structure

As standard, the open frame modular panel pc can be deployed in equipment machines, but remove the mounting bracket and it becomes a standalone panel pc for use with a VESA mount or in a 19" rack.





Strong, Reliable and Durable

Meets the requirements for HMI applications in harsh industrial environments: IP65 waterproof and dustproof front panel, fanless, wide temperature, and wide voltage (9–48 VDC).

IP65

CO-W121C Specifications

Model Name	CO-W121C
Display	
LCD Size	▪ 21.5" (16:9)
Resolution	▪ 1920 x 1080
Brightness	▪ 300 cd/m2
Contrast Ratio	▪ 5000 : 1
LCD Color	▪ 16.7M
Pixel Pitch	▪ 0.24825 (H) x 0.24825 (V) mm
Viewing Angle	▪ 178 (H) / 178 (V)
Backlight LED Life Time	▪ 50,000 hrs
Touch Screen	
Touchscreen Type	▪ Projected Capacitive Touch
Wet Touch Tracking	v
Physical	
Dimension (W x D x H)	▪ 550 x 343.7 x 63.3
Weight	▪ 7.16 kg
Construction	▪ One-piece and Slim Bezel Design
Mounting Type	▪ Flat / Standard / VESA / Rack Mount
Mounting Bracket	▪ Pre-installed Mounting Bracket with Adjustable Design (Support 11 different stages of adjustment)
Power	
Power Consumption	▪ 24.8W (Max.)
Protection	
Ingress Protection	▪ Front Panel IP65 Compliant * According to IEC60529
Environment	
Operating Temperature	▪ 0°C to 60°C (32°F to 140°F) (With Industrial Grade Peripherals; Ambient with air flow)
Storage Temperature	▪ -20°C to 60°C (-4°F to 140°F)
Humidity	▪ 90% RH @ 40°C (Non-condensing)
EMC	▪ CE, UKCA, FCC, ICES-003 Class A
EMI	▪ CISPR 32 Conducted & Radiated: Class A ▪ EN/BS EN 55032 Conducted & Radiated: Class A ▪ EN/BS EN IEC 61000-3-2 Harmonic current emissions: Class A ▪ EN/BS EN61000-3-3 Voltage fluctuations & flicker ▪ FCC 47 CFR Part 15B, ICES-003 Conducted & Radiated: Class A
EMS	▪ EN/IEC 61000-4-2 ESD: Contact: 4 kV; Air: 8 kV ▪ EN/IEC 61000-4-3 RS: 80 MHz to 1000 MHz: 3 V/m ▪ EN/IEC 61000-4-4 EFT: AC Power: 1 kV; DC Power: 0.5 kV; Signal: 0.5 kV ▪ EN/IEC 61000-4-5 Surges: AC Power: 2 kV; Signal: 1 kV ▪ EN/IEC 61000-4-6 CS: 3V ▪ EN/IEC 61000-4-8 PFMF: 50 Hz, 1A/m ▪ EN/IEC 61000-4-11 Voltage Dips & Voltage Interruptions: 0.5 cycles at 50 Hz
Safety	▪ UL, cUL, CB, IEC, EN 62368-1

P2002 Series Specifications


Model Name	P2002	P2002E
System		
Processor	▪ Onboard 6th Intel® Core™ U processors (Skylake) - Intel® Core™ i5-6300U processor (3M Cache, up to 3.00 GHz) - Intel® Core™ i3-6100U processor (3M Cache, 2.30 GHz) - TDP: 15 W	
Memory	▪ 2x DDR4 2133 MHz 260-Pin SO-DIMM Socket ▪ Support Un-buffered and Non-ECC Type up to 32 GB	
BIOS	▪ AMI 64Mbit SPI BIOS	
Graphics		
Graphics Engine	▪ Integrated Intel® UHD Graphics 520	
Maximum Display Output	▪ Supports Triple Independent Display	
CDS	▪ 1x CDS Connector for Cincoze Display Module	
VGA	▪ 1x VGA Connector(1920 x 1080 @60Hz), DB-15	
DVI-D	▪ 1x DVI-D Connector (1920 x 1080 @ 60Hz)	
Audio		
Audio Codec	▪ Realtek® ALC888, High-Definition Audio	
Speaker-out	▪ 1x Speaker-out, Phone Jack 3.5mm	
Mic-in	▪ 1x Mic-in, Phone Jack 3.5mm	
I/O		
LAN	▪ 2x GbE LAN (Supports WoL, Teaming, Jumbo Frame & PXE), RJ45 - GbE1: Intel® I219LM - GbE2: Intel® I210	
USB	▪ 4x USB 3.2 Gen1 (Type A), 1x USB 2.0 (Type A)	
Serial Port	▪ 6x RS-232/422/485 with Auto Flow Control Support 5V/12V, DB9	
DIO	▪ 16x Isolated Digital I/O (8in/8out), 10-Pin Terminal Block	
Storage		
SSD/HDD	▪ 2x 2.5" HDD/SSD Bay, Support RAID 0/1 (Gen3)	
mSATA	▪ 2x mSATA (One Shared by Mini-PCIe Socket) (Gen2)	
CFast	▪ 1x CFast Socket (Gen 3)	
Expansion		
Mini PCI Express	▪ 2x Full-size Mini-PCIe Sockets	
PCI Express		▪ 1x PCI or 1x PCIe x4 Expansion slot (with Optional Riser Card) ▪ maximum dimension of add-on card:100mm x 200mm (H x L)
SIM Socket	▪ 1 x Front Accessible SIM Socket	
Universal Bracket	▪ 1x Universal I/O Bracket	
CFM (Control Function Module) Interface	▪ 2x CFM Interface for optional CFM-IGN or CFM-PoE (max 25.5W) Module Expansion	
CDS (Convertible Display System) Technology	▪ 1x Convertible Display System (CDS) Interface, Compact PCI Connector	

Other Function		
Instant Reboot	▪ Support 0.2sec Instant Reboot technology	
Watchdog Timer	▪ Software Programmable Supports 256 Levels System Reset	
Internal Speaker	▪ AMP 2W + 2W	
OSD Function	▪ LCD On/Off, Brightness Up, Brightness Down	
Reset Button	▪ 1x Reset Button	
External Fan Connector	▪ 1x External Fan Connector, 4-pin Terminal Block	
Power		
Power Button	▪ 1x ATX Power On/Off Switch	
Power Mode Switch	▪ 1x AT/ATX Mode Switch	
Power Input	▪ 1x 3-pin Terminal Block Connector with Power Input 9~48VDC	
Power Adapter (Optional)	▪ 1x Optional AC/DC 12V/5A 60W or 24V/5A 120W ▪ 1x Optional AC/DC 24V/9.2A 220W (For P2002E only)	
Remote Power On/Off	▪ 1x Remote Power On/Off Connector, 2-pin Terminal Block	
Physical		
Dimension(W x D x H)	▪ 254.5 x 220 x 54mm	▪ 254.5 x 220 x 72 mm
Weight Information	▪ 2.92 kg	▪ 3.18 kg
Mechanical Construction	▪ Extruded Aluminum with Heavy Duty Metal	
Mounting	▪ Wall / VESA / CDS	
Physical Design	▪ Fanless Design ▪ Jumper-less Design	
Reliability & Protection		
Reverse Power Input	▪ Yes	
Over Voltage Protection	▪ Protection Range: 51~58V ▪ Protection Type: shut down operating voltage, re-power on at the present level to recover	
Over Current Protection	▪ 15A	
CMOS Battery Backup	▪ SuperCap Integrated for CMOS Battery Maintenance-free Operation	
Operating System		
Microsoft® Windows®	▪ Windows® 10, Windows® 8.1, Windows® 7	
Linux	▪ Linux® Kernel 4.4	
Environment		
Operating Temperature	▪ Ambient with Air Flow: -25°C to 70°C (with Extended Temperature Peripherals)	
Storage Temperature	▪ -40°C to 85C	
Relative humidity	▪ 95% RH @ 40˚C (Non-condensing)	
Shock	▪ Operating, 50 Grms, Half-sine 11ms Duration (w/ SSD, according to IEC60068-2-27)	
Vibration	▪ Operating, 5 Grms, 5-500 Hz, 3 Axes (w/ SSD, according to IEC60068-2-64)	
EMC	▪ CE, UKCA, FCC, ICES-003 Class A	


EMI	▪ CISPR 32 Conducted & Radiated: Class A ▪ EN/BS EN 55032 Conducted & Radiated: Class A ▪ EN/BS EN IEC 61000-3-2 Harmonic current emissions: Class A ▪ EN/BS EN61000-3-3 Voltage fluctuations & flicker ▪ FCC 47 CFR Part 15B, ICES-003 Conducted & Radiated: Class A
EMS	▪ EN/IEC 61000-4-2 ESD: Contact: 4 kV; Air: 8 kV ▪ EN/IEC 61000-4-3 RS: 80 MHz to 1000 MHz: 3 V/m ▪ EN/IEC 61000-4-4 EFT: AC Power: 1 kV; DC Power: 0.5 kV; Signal: 0.5 kV ▪ EN/IEC 61000-4-5 Surges: AC Power: 2 kV; Signal: 1 kV ▪ EN/IEC 61000-4-6 CS: 3V ▪ EN/IEC 61000-4-8 PFMF: 50 Hz, 1A/m ▪ EN/IEC 61000-4-11 Voltage Dips & Voltage Interruptions: 0.5 cycles at 50 Hz

CO-W121C/P2002 External Layout


Front I/O




Rear I/O



Left I/O




Right I/O




CO-W121C/P2002E External Layout


Front I/O




Rear I/O




Left I/O



Right I/O




CO-W121C/P2002 Dimensions



Installation Schematic

CO-W121C/P2002E Dimensions



Installation Schematic

Unit: mm

Ordering Information

Available Models

Model No.	Description
CO-W121C-R10/P2002-i5-R10	21.5" TFT-LCD Full HD 16:9 Open Frame Display Module with Projected Capacitive Touch and Intel 6th Gen. Core i5-6300U Fanless Computer, CFM Interface, CDS Interface
CO-W121C-R10/P2002E-i5-R10	21.5" TFT-LCD Full HD 16:9 Open Frame Display Module with Projected Capacitive Touch and Intel 6th Gen. Core i5-6300U Expandable Fanless Computer, CFM Interface, CDS Interface
CO-W121C-R10/P2002E-i5-E4-R10	21.5" TFT-LCD Full HD 16:9 Open Frame Display Module with Projected Capacitive Touch and Intel 6th Gen. Core i5-6300U Fanless Computer, CFM Interface, CDS Interface, 1x PCIex4 Expansion
CO-W121C-R10/P2002E-i5-PI-R10	21.5" TFT-LCD Full HD 16:9 Open Frame Display Module with Projected Capacitive Touch and Intel 6th Gen. Core i5-6300U Expandable Fanless Computer, CFM Interface, CDS Interface, 1x PCI Expansion
CO-W121C-R10/P2002-i3-R10	21.5" TFT-LCD Full HD 16:9 Open Frame Display Module with Projected Capacitive Touch and Intel 6th Gen. Core i3-6100U Fanless Computer
CO-W121C-R10/P2002E-i3-R10	21.5" TFT-LCD Full HD 16:9 Open Frame Display Module with Projected Capacitive Touch and Intel 6th Gen. Core i3-6100U Expandable Fanless Computer, CFM Interface, CDS Interface
CO-W121C-R10/P2002E-i3-E4-R10	21.5" TFT-LCD Full HD 16:9 Open Frame Display Module with Projected Capacitive Touch and Intel 6th Gen. Core i3-6100U Fanless Computer, CFM Interface, CDS Interface, 1x PCIex4 Expansion
CO-W121C-R10/P2002E-i3-PI-R10	21.5" TFT-LCD Full HD 16:9 Open Frame Display Module with Projected Capacitive Touch and Intel 6th Gen. Core i3-6100U Expandable Fanless Computer, CFM Interface, CDS Interface, 1x PCI Expansion

Model Configuration

	CO-W121C	P2002 (i3/i5)	P2002E (i3/i5/E4/PI)
CO-W121C/P2002	V	V	--
CO-W121C/P2002E	V	--	V

V : Compatible


Package Checklist

- CO-W121C/P2002 Series Panel PC x 1
- Wall / CDS Mounting Kit x 1
- Power Terminal Block Connector x 1
- Fan Terminal Block Connector x 1
- DIO Terminal Block Connector x 2
- Remote Power On/Off Terminal Block Connector x 1
- Screw Pack x 1


Model No.	Description
RC-PI-01	Riser Card with 1x PCI Slot(For P2002E only)
UB0503	Universal Bracket with 2x DB9 Cutout
UB0504	Universal Bracket with 4x DB9 Cutout
UB0511	Universal Bracket with 2x RJ45 Cutout
UB0514	Universal Bracket with 2x USB Cutout
URM01	Universal 19" Rack Mount Kit for Industrial Panel PC & Industrial Monitor
GST220A24-CIN	Adapter AC/DC 24V 9.2A 220W with 3pin Terminal Block Plug 5.0mm Pitch, with TUBES, GST220A24-CIN
GST120A24-CIN	Adapter AC/DC 24V 5A 120W, GST120A24-CIN, wide temp(-30°C ~ +70°C), level VI
GST60A12-CIN1	Adapter AC/DC 12V 5A 60W, GST60A12-CIN1, wide temp(-30°C ~ +70°C)
SL2-SL3	US 2 heads power cord, US B type to IEC C13,SVT 18AWG/3C Black 1.8M
SL6-SL3	EU 2 heads power cord, EU G type to IEC C13,H05VV-F 0.75mm2/3G Black 1.8M
QP026-SL3	UK 2 heads power cord, UK I type to IEC C13,H05VV-F 0.75mm2/3G Black 1.8M

Optional Module Configuration

P2002



P2002E



Model No.	Description	P2002	P2002E
MEC-COM-M212/UB0503 	Mini-PCIe Module with 2x COM Ports, 1x Universal Bracket with 2x DB9 Cutout (154 x 17 mm)	V	V
MEC-COM-M334/UB0504 	Mini-PCIe Module with 4x RS-232/422/485 Serial Ports, 1x Universal Bracket with 4x DB9 Cutout (154 x 17 mm)	V	V
MEC-LAN-M102-30/UB0511 	Mini-PCIe Module with 2x LAN Ports, 2x 30cm cable, 1x Universal Bracket with 2x RJ45 Cutout (154 x 17 mm)	V	V
MEC-USB-M102-30/UB0514 	Mini-PCIe Module with 2x USB 3.0 Ports, 1x Universal Bracket with 2x USB Cutout (154 x 17 mm)	V	V

V : Compatible

Updated: Aug. 29, 2025.

© Cincoze Co., Ltd. All Rights Reserved. Specifications subject to change without notice.
All product names, logos, and brands are the property of their respective owners. All company, product and service names used in this document are for identification purposes only. The use of these names, logos, and brands does not imply endorsement.